




## ISO metric thread (with end) ISO метрическая резьба (полный профиль)


Internal thread / Внутренняя резьба



Y type



Z type



Type		Dimensions(mm)				Grade	
The right hand tools	The left hand tools	螺距 Pitch	S	ØI.C	ød	KLT115	
						R	L
YT11.01N-0.50GM	ZT11.01N-0.50GM	0.50	3.18	6.35	2.8	○	○
YT11.01N-0.75GM	ZT11.01N-0.75GM	0.75	3.18	6.35	2.8	○	○
YT11.01N-1.00GM	ZT11.01N-1.00GM	1.00	3.18	6.35	2.8	○	○
YT11.01N-1.25GM	ZT11.01N-1.25GM	1.25	3.18	6.35	2.8	○	○
YT11.01N-1.50GM	ZT11.01N-1.50GM	1.50	3.18	6.35	2.8	★	○
YT11.01N-1.75GM	ZT11.01N-1.75GM	1.75	3.18	6.35	2.8	○	○
YT11.01N-2.00GM	ZT11.01N-2.00GM	2.00	3.18	6.35	2.8	★	○
YT16.01N-0.50GM	ZT16.01N-0.50GM	0.50	3.97	9.525	4.4	○	○
YT16.01N-0.75GM	ZT16.01N-0.75GM	0.75	3.97	9.525	4.4	○	○
YT16.01N-1.00GM	ZT16.01N-1.00GM	1.00	3.97	9.525	4.4	★	○
YT16.01N-1.25GM	ZT16.01N-1.25GM	1.25	3.97	9.525	4.4	○	○
YT16.01N-1.50GM	ZT16.01N-1.50GM	1.50	3.97	9.525	4.4	★	★
YT16.01N-1.75GM	ZT16.01N-1.75GM	1.75	3.97	9.525	4.4	○	○
YT16.01N-2.00GM	ZT16.01N-2.00GM	2.00	3.97	9.525	4.4	★	★
YT16.01N-2.50GM	ZT16.01N-2.50GM	2.50	3.97	9.525	4.4	★	★
YT16.01N-3.00GM	ZT16.01N-3.00GM	3.00	3.97	9.525	4.4	★	★
YT22.01N-3.50GM	ZT22.01N-3.50GM	3.50	5.56	12.7	5.5	○	○
YT22.01N-4.00GM	ZT22.01N-4.00GM	4.00	5.56	12.7	5.5	★	○
YT22.01N-4.50GM	ZT22.01N-4.50GM	4.50	5.56	12.7	5.5	○	○
YT22.01N-5.00GM	ZT22.01N-5.00GM	5.00	5.56	12.7	5.5	★	○
YT22.01N-5.50GM	ZT22.01N-5.50GM	5.50	5.56	12.7	5.5	○	○
YT22.01N-6.00GM	ZT22.01N-6.00GM	6.00	5.56	12.7	5.5	★	○

★ Recommended grade

● Available grade

○ Make-to-order